



IP54-RFL125SM

Project:	Type:	QTY:
Product Code:		

Ø5" OD



Product Code

IP54 - RFL125SM -	BODY COLOR	-	LED COLOR	-	VOLTAGE
	W=White		WW27 =2700K WW30*=3000K WW35 =3500K NW40 =4000K		120=120V

Note: * Components usually in-stock for quick assembly and shipping.

Features + Specifications

Intended Use:

- Building interior, protected exterior
- Wet location listed (ceiling mount)

Construction:

- Aluminum mounting base for heat management
- Injection plastic trim ring
- Opal PMMA lens blocks out LED diodes image
- Metal mounting bracket fits and mount to 4" oct box
- No screws snap in mounting to mounting bracket

Optical System:

- Multiple 2835 SMDs integrated light engine
- Light engine PCB mounted onto aluminum base
- PMMA opal lens seals to injection plastic trim ring
- LEDs with LM80 certification and TM21 life rating
- 3000K 90CRI, 900+lm, 9W system watt, 110° light distribution
- Other CCTs available, please consult factory for MOQ

Specifications subject to change without notice



Certified to CSA C22.2 No.250.0 Conformed to UL 1598 | Certification marks (where applicable) will be found on our luminaires and its components

iplighting.com



IP54-RFL125SM

Custom Lighting Design & Manufacture

Electrical System:

- HPF high efficiency integrated driver on board design
- Low THD, short circuit and overheat protected
- 120V line voltage dimmable
- RoHS compliant

Mounting:

- Mounting bracket fits octagon ceiling box
- Unit comes with snap in screwless mounting spring
- Mounting spring mate with mounting bracket without use of tools

Dimension:

